



3 1 0 0 C O R O N E T



STANDARDS / OPTIONS 2011 MODEL YEAR

EFFECTIVE MAY 2, 2011

PRINTED IN USA

3100 CORONET

STANDARD EQUIPMENT



SPECIFICATIONS

L.O.A. without Standard Pulpit ...
30'6" - 9.29 meters

L.O.A. with Standard Pulpit ...
33'1" - 10.08 meters

L.O.A. with Standard Pulpit and Standard
40" Swim Platform ... 36'5" - 11.1 meters

Beam ... 12'6" - 3.81 meters

Draft (with Props) ... 2'8" - 0.8 meters

Approximate Dry Weight ...
13,550 lbs. - 6,146 kg (gas)

Height from Waterline to Top of
Standard Arch ... 8'0" - 2.44 meters

Height from Waterline to Top of
Optional Hardtop ... 8'3" - 2.52 meters

Standard Fuel Capacity ...
210 U.S. gallons - 794.94 liters

Water Capacity ...
33 U.S. gallons - 124.92 liters

Holding Tank Capacity ...
20 U.S. gallons - 75.71 liters

Sleeping Accommodations ... 2

Headroom ... 5'8" - 1.73 meters

Deadrise at Transom ...14°

HULL AND DECK

- Tiara Yachts' transferable limited warranties: five years on hull, deck and fiberglass fuel tank; two years on accessories. Exclusions apply - refer to 2011 warranty statement for specific details and coverage areas.
- Fresh white gelcoat hull and deck
- Imron® platinum bootline
- Hull constructed with a gelcoat outer layer, balsa cored hullsides, and hand-laid fiberglass using a premium resin
- Deck constructed with a gelcoat outer layer, coring, and hand-laid fiberglass using a premium resin
- Tiara custom diamond pattern non-skid deck and cockpit surfaces
- Stringers, encapsulated by hand-laid fiberglass, are integrated to the hull
- Gelcoated bilge
- Bronze seacocks on all underwater thru-hull fittings

- Molded-in hullside engine room ventilation
- Lenco® electro-mechanical trim tabs with indicator lights at helm
- Four (4) S.S. opening port lights with screens and privacy inserts
- One (1) Bomar® low profile extruded aluminum forward deck hatch with adjuster and built-in Ocean Air® screen and privacy cover
- Molded-in self draining fiberglass bow pulpit with S.S. roller
- One-piece welded 316L S.S. 1" bow rail with pulpit, staff, and Tiara burgee
- Flush forward anchor rode locker with overboard drain
- Automatic rope/chain anchor windlass system with operation from foredeck foot pedal and remote switch at helm. Includes one (1) 8" S.S. foredeck cleat, 30' chain rode, 200' rope rode, and Delta® 14 lb. galvanized anchor
- White rubrail with 316L S.S. cap
- Four (4) 10" S.S. cleats forward/midship and two (2) 10" pop-up cleats aft
- Radar arch
- Single level cockpit floor
- Two-tone exterior vinyl (neutral color scheme)

COMMAND BRIDGE

- Tiara custom composite windshield frame with tempered safety glass and a windshield wiper system with two (2) washer/wipers
- Centerline entry to salon with acrylic sliding companionway door, screen, lock, and privacy cover
- Tiara hinged helm console with full flush mount electronics capability, one (1) drink holder, 12V outlet, and 16" S.S. destroyer steering wheel
- Helm seat with manual adjustment and storage locker below
- Entertainment center with TV jack, electric grill, sink, and 2.6 cu. ft. drawer refrigerator (wired DC)
- 120V GFI outlet
- Curved companion lounge with storage below and teak table
- Drop-down engine room access hatch from the command bridge

AFT COCKPIT & TRANSOM

- Molded-in steps to deck walkways, port and starboard
- Cockpit LED courtesy lighting
- Cockpit shower, hot and cold water
- Port and starboard aft L-lounges with storage below
- Two (2) aft facing seats/lounges
- Molded-in centerline transom door
- 40" swim platform with built-in ladder

INTERIOR GROUP

- Mold and mildew resistant vinyl hull and headliner treatment
- Teak interior - *NOTE: Variations in Teak wood grain are natural, and cannot be controlled in the manufacturing process*
- Solid teak cabin sole
- Cable TV jack
- 120V outlets throughout
- 12V LED lighting
- 5'8" headroom
- Companionway steps with teak treads and courtesy lights
- S.S. companionway handrail (port)
- Clarion® AM/FM/CD stereo with cockpit remote, 2 channel amplifier, two (2) 6.5" interior speakers and two (2) 6.5" cockpit speakers, and MP3 interface.
- Cedar-backed port locker with hanging rod

GALLEY

- Corian® countertop with stainless steel sink
- Utensil drawer
- Microwave oven

FORWARD BERTH

- Pedestal berth and storage below. Foam mattress with fabric cover.
- Two (2) reading lights, independently switched

HEAD

- Full fiberglass head with shower sump pump and shower curtain
- Vanity with Corian® countertop, stainless steel sink and storage below
- Mirror
- Vacuflush® toilet
- Exhaust blower and A/C vent

INSTRUMENTATION, EQUIPMENT AND SAFETY

- Tiara 12V and 120V distribution panels. The 120V panel is located under the companionway steps and the 12V panel is split between the companionway steps and the port hanging locker.
- One (1) 120V 30 amp 65 ft. dockside power cord, inlet located starboard
- Cable TV inlet and cabin outlet with 65 ft. dockside power cord
- AM/FM antenna
- Battery charger (1), 30 amp
- Two bank 12V battery system with batteries and battery switches (two (2) engine batteries and two (2) house batteries)
- Reverse polarity indicators
- Amp meters, AC and DC
- Electrical bonding system
- Zincs - transom and shafts

- Teleflex® twin mechanical engine controls (gas engines)
- Teleflex® hydraulic steering system
- Bronze axe head rudders and struts
- Aquamet® S.S. prop shafts, 1 3/8" (gas engines)
- Water cooled shaft logs with PSS® dripless shaft seal
- Two (2) Nibral® propellers
- Engine instrumentation: Crusader® engine option includes tachometers w/ hour meters, voltage gauges, fuel gauge, temperature gauges, and engine oil pressure gauges.
- Ritchie® Helmsman HF-743 compass
- High output alternators, 70 amps each for Crusader® gas engines
- Engine room acoustical insulation
- Engine hatch actuators
- 12V engine room lights
- Two (2) Crusader® fuel filters/water separators (gas engines)
- Two (2) raw water intake strainers
- Vibration isolating engine mounts
- Plate mounted, thru-bolted engine system
- Two (2) bilge blowers, 250 CFM each
- Three (3) bilge pumps with monitors at helm: One (1) 500 GPH automatic forward, one (1) 2000 GPH automatic/manual mid, and one (1) 2000 GPH automatic/manual aft
- One (1) composite fuel tank, 210 gallons, with electric gauge and fuel shut-off valve on top of tank

- Dockside water inlet
- One (1) fresh water tank, 33 gallons, with monitor
- Fresh water pressure system
- One (1) holding tank, 20 gallons, with indicator light located in the head
- One (1) water heater with exchanger, six (6) gallons
- Air horn
- FE-241 agent automatic/manual fire extinguisher system in engine room (HFC-227ea for Europe)
- Two (2) handheld fire extinguishers
- One (1) carbon monoxide detector
- One (1) smoke detector
- Four (4) 5/8" x 25' black dock lines
- Four (4) Tiara life vests (domestic boats only)
- USCG safety and medical kit
- USCG/international navigation lighting
- NMMA certified using ABYC standards
- International certification options available (European CE and others)

