

FERRETTI
480



SPECIFICATIONS

ENGINES

2 MAN D2876 LE 404 6L, power 630 mhp (463 kW) at 2200 rpm

SPEED WITH BOAT FULLY LADEN

Maximum speed - knots
Cruising speed - knots

MAN 630

31.5
27

TECHNICAL DATA

Hull type: warped with 14.6 degree deadrise
and hydrodynamic support spray rails

Lh=Hull length (ISO 8666)

Loa=Overall length (ISO 8666)

Maximum beam

Draft below propellers at full load

Displacement at full load

Maximum number of people aboard (R.I.Na. homologation)

Fuel tank capacity

Water tank capacity

47 ft. 7 in. / 14.50 m.

48 ft. 7 in. / 14.80 m.

15 ft. 1 in. / 4.60 m.

4 ft. 9 in. / 1.43 m.

44321 lb. / 20.1 ton.

14

502 US gals. / 1900 lt.

185 US gals. / 700 lt.

CARATTERISTICHE TECNICHE

MOTORIZZAZIONE

2 MAN D2876 LE 404 6L, potenza 630 mhp (463 kW) a 2200 g/min

VELOCITÀ A PIENO CARICO

Velocità massima - nodi
Velocità di crociera - nodi

MAN 630

31,5
27

DATI CARATTERISTICI

Tipo di carena: warped con deadrise 14,6°

e pattini di sostentamento idrodinamico

Lh=Lunghezza di costruzione (ISO 8666)

Loa=Lunghezza fuori tutto (ISO 8666)

Larghezza massima

Immersione sotto le eliche a pieno carico

Dislocamento a pieno carico

Numero massimo di persone imbarcabili (om. R.I.Na.)

Capacità serbatoi carburante

Capacità serbatoi acqua

14,50 m.

14,80 m.

4,60 m.

1,43 m.

20,1 ton.

14

1900 lt.

700 lt.

