

LeisureCat 6000 Islander

General Features

- LOA (including engines): 6.89 metres (22 ft 7 in)
- Moulded Length: 6.0 metres (19 ft 8 in)
- Beam: 2.55 metres (8 ft 4 in)
- Draught: 0.40 metre (1 ft 3 in)
- Fuel Storage: 300 litre (79 gal/US)
- Power (min. recom.): 2 x 70 hp Outboards.
- Aquaguard Gelcoat used in laminate.
- Fully-sealed, non-skid deck.
- Twin heavy-duty battery switches in console.
- Fibreglass lids with stays on storage area port and starboard.
- Open storage areas x 4 in coamings.
- Watertight hatches to moulded engine well areas.
- Fully moulded engine wells included in hulls.
- Full length wave breaker.
- Hull solid single-skin construction with reinforced frames and laminated transom to suit engine selection.
- Superstructure and cockpit deck moulding.
- Solid single-skin and sandwich (foam core) construction including localized reinforcing for deck hardware.
- Mould to incorporate walk-around cabin and twin front seat moulding.
- Rubber gunwale rub rail.
- Moulded console housing controls, electronics, radios.
- Storage under front bench seat (hinged top).



- FRP bulkheads (5) below deck - forward collision bulkhead watertight.
- FRP footrests (2) to console.
- Two(2) FRP fuel tanks - 150 litres per side (total 300 litres) fitted with tank level senders.
- Windscreen in smoked acrylic with anodised frames.
- Foredeck sun-lounge with white UV cushion.
- S/s bow roller.
- S/s main deck bollard - split with pin.
- S/s hand rail to console.
- S/s catches and hinges throughout.
- Set of stern (x2) and midship (x2) cross bollards fitted.
- S/s fuel deck filters (x2).
- S/s recessed fuel tank breathers (x2).



Mechanical and Electrical

- Plumb fuel lines and fitted fuel/water filters.
- Binnacle station controls as supplied with engine package.
- Single station hydraulic outboard steering package with wheel.
- Two (2) 12 volt 2000gph electric bilge pumps fitted to motor well compartments with sure-bail float switches.
- Bilge lines to discharge overboard through non-return valves.
- Complete 12 volt electrical installation including all materials, switches, lights, tags, etc.
- Navigation lights and anchor light.
- BEP 6-gang DC splashproof switch fuse panel fitted at helm.



Options

- Stainless steel bow rail.
- S/s rail around windscreen with rod holders.
- Soft-top with stainless steel frame.
- Hard-top with stainless steel frame.
- Freshwater supply.
- Removable Helm bench seating with UV cushion.
- Swivel single seating on moulded base.
- Carpeted deck.
- Live-bait tank fitted to rear coaming.
- Decals and stripes.
- Saltwater deck wash.
- S/s hinged dive ladder.
- S/s targa frame.
- Side bolsters.

Safety Equipment

- All under-floor compartments fitted with closed cell foam flotation as practicable.
- Fire extinguisher in moulded recess.
- Ritchie Explorer flush-mount compass.
- EPIRB - 121/243MHz in moulded recess.



All LeisureCat/AussieCats have a 4-year structural warranty on hull and deck

Note: LeisureCat/AussieCat Australia Pty Ltd strive continually to improve features and retain the right to alter any or all of these specifications without notice.



Proudly built in Western Australia by

LeisureCat Australia

23a Possner Way, Henderson, WA, Australia, 6166

Phone: 61-8-9410 0888

Fax: 61-8-9410 1888

Email: sales@leisurecat.com.au

Web Sites: <http://www.leisurecat.com.au>

<http://www.aussiecat.com.au>