



F – 0243 RORO-PAX- CAR FERRY

BUILT: 1998.02 , DAEWOO HEAVY INDUSTRIES LTD. KOREA
 DIMS: 114.5/107.6 X 20 X 11.05 M
 CLASS: KR
 SOLAS CERT FOR SHORT INT'L VOYAGE
 SS/DD: LAST SS/DD – FEBR. 2008 , NEXT SS = FEB. 2013
 TONNAGE: 4,166 T (GRT 9,088 MT INTERNATIONAL)
 DWT: 1,690 MT ON 4.75 M DRAFT
 M/E: SSANGYONG MAN B&W 4,800 PS X 2 SETS
 A/E : MAN B&W 880 PS X 3 SETS
 SPEED : DESIGNED SERVICE 17,8 KNTS,
 USUAL PERFORMED SERVICE SPD IS ABOUT MIN 18 KTS AT
 85% MCR. MAXIUM 19.8 KNTS

PASSENGER : 720 PERSONS
 TRUCK : 36 UNITS IN MAIN DECK
 PASSENGER CAR : 50UNITS IN CAR DECK
 PROPELLER : FPP 5 BLADES
 RAMPWAY : BOW, STERN QUARTER, STB'D SIDE.
 BOW THRUSTER : FITTED
 FIN STABILIZER : FITTED

+++++

PASSENGER BREAKDOWN

+++++

VIP 8 X 2 P = **16 P**

 1ST CLASS 10 X 2 P = **20 P**

2ND CLASS 8 X 3 P = 24 P
 (BED ROOM) 22 X 6 P = 132 P
 14 X 4 P = 56 P **SUB TOTAL : 312 P**

3RD CLASS 8 X 9 P = 72 P
 (Floor Room) 2 X 8 P = 16 P

6 X10 P = 60 P **SUB TOTAL : 148 P**

SEATS: 324 P

GRAND TOTAL 720 P

+++++

PUBLIC FACILITIES BREAKDOWN

+++++

Q'TY	KIND	CAPACITY	AREA
1	VIP SALOON	15 P	58.05 M2
1	RESTAURANT	70 P	226.25 M2
1	EVENT HALL	84 P	110.00 M2
3	FUNCTION ROOM	34 P	76.00 M2
1	SOUVENIR SHOP		53.00 M2
1	NIGHT CLUB	100 P	202.57 M2
1	BAR	68 P	161.12 M2
6	KARAOKE	32 P	58.75 M2
1	LOUNGE		195.20 M2

+++++

TRUCK CAPACITY

+++++

10.0 (L) X 2.5 (B) X 3.1(H)M : 36 UNIT

LANE LENGTH(ABT) : 380 M

DECK HEIGHT : 4.80 M

+++++

RAMP

+++++

1) Configuration

- . 1 - Bow visor and Bow Ramp
- . 1 - Stern Main Ramp
- . 1 - Stern Passenger car Ramp
- . 1 - Side Ramp

2) Bow Visor

- . Non-tight steel construction
- . Operating : Two Hydraulic Cylinders for Open/Close .Locking : Two Hydraulic Cylinders & Manual Locking Devices .Stopper : Wedge type stopper

3) Bow Ramp

- . Water-tight Steel Construction and Enclosed box type .Ramp Size :
No.1 (4.8 (L) x 5.15 m (B)),
No.2 (5.95 (L) x 5.0 m (B))
Flap (1.7 (L) x 4.9 m (B)) .S.W.L : 25 ton

4) Stern Main Ramp

- .Water-tight Steel Constructin and Enclosed box type .Ramp Size :
No.1(6.9 (L) x 6.4 m (B)), No.2 (7.4 (L) x 7.0 m (B)) .S.W.L : 40 ton

5) Stern Passenger Car Ramp

.Water-tight Steel Construction and Enclosed box type .

Ramp Size : No.1 (7.2 (L) x 3.35 m (B)),
No.2 (7.4 (L) x 4.20 m (B)) .S.W.L : 2 ton

6) STB'D Side Ramp

.Water-tight Steel Construction

. Ramp size : 4.1 (L) x 4.8 m (B) , .S.W.L : 40 ton

FUEL OIL CONSUMPTION (AT MCR) : 142 G/PS.HR +/- 3%

+++++

BOW THRUSTER

+++++

.MAKER : BRUNVOLL(NORWAY)

.MODEL: FU-63-LTC-1750

.THRUSTER : 89KN(NORMAL VALUE)

.Input speed on thruster : 1,780 rpm

.Input Power on thruster : 816 Hp, (640 KW) .Electric motor : ABB M2FA 355 LA4

+++++

FIN STABILIZER

+++++

.Maker : BLOHM + VOSS(Germany)

.Model : S300

.Number of Fins: 2

.Efficiency fin area : 4.2 m2

.Max working angle of main fins : +/-18 deg .Finangle reduction from : 17.5 knots

.Extending or housing time of fins: abt.90 sec

+++++

FAST RESCUE BOAT

+++++

6 Persons x 1(20 knts) Set

+++++

LIFE RAFTS

+++++

25 Persons x 33 set

12 Persons x 2 set

+++++

LOCATION: KOREA , WHERE PROMPT INSPECTABLE

+++++

OWNERS ASKING: USD 19.0 MILL. NET , AS IS – WHERE IS

- ALL DETAILS GIVEN TO BE CORRECT BUT NOT GUARANTEED , FULL DETAILS INCLUDING PLANS AND RECENT PHOTOS ON NAMED BUYERS REQUEST -