




OLYMPIC

Welcome on board!



500 C



OLYMPIC
Boats

MAJANUOVANAUTICA
34148 - TRIESTE
338-2309461 / 040-9896814
www.majanuovanautica.it
e-mail: info@majanuovanautica.it

SPECIFICATIONS

Overall length	5,44 m
Hull length	4,98 m
Overall beam	2,15 m
Weight	500 kg
Power	50-100 hp
Passengers	6 persons
Hull deadrise at transom	18°

STANDARD EQUIPMENT

- Curved safety-glass windshield
- Steering wheel
- Steering mechanism
- Steering cable
- Electrical panel
- Electrical auto fuses
- Electrical switches w. twin indicator lights
- Battery On/Off switch
- Navigation lights
- Cabin lights
- Bilge pump 500gph
- Driver swivel seat
- Anchor roller
- 4 s/steel cleats 6"
- Full cabin set cushions
- Bow eye
- Bow rails
- Cabin hatch
- Cabin carpet

CONSTRUCTION FEATURES

- Two-tone gelcoat
- Self bailing cockpit
- Unsinkable
- Cabin and aft storage compartments
- Anchor storage compartment in bow
- 5-year structural hull warranty
- Marine grade vinyls
- Colour coded electrical system
- CE certification

SPECIFICHE TECNICHE:

Lunghezza f.t.:	5,44 mt.
Lunghezza omologazione:	4,98 mt.
Larghezza:	2,15 mt.
Peso:	500 kg
Potenza applicabile:	50-100 hp
Persone:	6
Angolo di poppa:	18°

Allestimento standard:

- Parabrezza vetro temperato infrangibile
- Ruota del timone personalizzata olympic
- Timoneria
- Cavo timoneria
- Pannello elettrico
- Interruttori magnetotermici
- Interruttori con indicatore luminoso
- Stacca batteria
- Luci di via
- Illuminazione in cabina
- Pompa di sentina da 500gph
- Seduta di governo girevole
- Musone di prua
- 4 bitte da 6"
- Cuscineria di cabina completa
- Anello di prua
- Tientibene di prua
- Chiusura cabina
- Moquette in cabina

CARATTERISTICHE COSTRUTTIVE

- Gelcoat a due colori
- Seduta di governo ergonomica
- Innafondabile e autosvuotante
- Gavoni di poppa e in cabina
- Gavone ancora
- 5 anni di garanzia strutturale dello scafo
- Vinile marino
- Impianto elettrico codificato a colori
- Certificazione CE

CONCESSIONARIO DI ZONA:

LE SPECIFICHE SONO SOGGETTE A MODIFICHE SENZA PREAVVISO
Specifications are subject to change without prior notice.