

CSL 27

Cat. SPORT LINE

Technical profile

Length-overall	28 ft 1 in approx.
Length-hull	24 ft 8 in approx.
Length-waterline	20 ft 7 in approx.
Beam – max	9 ft 5 in approx.
Beam – hull	9 ft 3 in approx.
Height above waterline (incl. light)	6 ft 9 in approx.
Draft (incl. props)	2 ft 10 in approx.
Dry weight	5,000 / 5,800 lbs approx.
Passengers	8 / 1,584 lbs approx.
Fuel capacity	76 UK gal / 86 US gal approx.
Fresh water capacity	16 UK gal / 19 US gal approx.
N° of berths	2
Hull	Aldo Cranchi
Project	Cranchi Research Development Department
Design category	B
Petrol engine options	Volvo Penta V6 2 x 4.3 EVC / MC GXi / DP-S Volvo Penta V8 5.7 EVC / MC GXi / DP-S (320 hp)
Diesel engine options	Volvo Penta D4 EVC / DP-H (260 hp)



Deck fittings:

N. 6 aisi 316 stainless steel cleats – Stainless steel bow eye – Stainless steel pulpit – Stainless steel handrails – N. 1 Hatch – N. 2 portholes (non opening) – Windschield with anodised frame and central opening – Bow access steps – Navigation lights – Ensign staff – Horn – S.s. fuel and water cap – Fuel tank air vent with anti-flame and antispray net – Stern hook – 2 stern eyes – Moduled non-slip surfaces on deck and side decks – Rubbing Band – N. 1 dashboard handrail.

Cockpit and helm console:

Self draining – Wet bar with cover and accomodation for refrigerator (extra) – Waste bin – Overturning pilot and copilot seats – Object holder – Storage Locker-table – Rear sunbather – Electrical engine room hatch (manual opening for emergency) – Shower (hot/cold) – Foldaway swimming ladder and handle – Lighting – Boathook – Owner's manual – N. 1 automatic fire extinguisher in the engine room – N. 1 manual fire extinguisher in the cockpit – **Helm console:** Radio CD (helm console control) – single lever engine control – electronic lever engine control for D4 version – Power steering/hydraulic steering for D4 version – Wood/leather steering wheel – BidataEcho-Log – Complete engine instruments: oil pressure gauge, water temp. gauge, volt meters, hourcounter, revs.counter, trim gauge – Fuel gauge – Ritchie compass – Horn control – Navigation lights control – 12v socket for cellular phone – Engine instrument light.

Cabin:

Sliding door – “U” form dinette – Power socket – Lighting – Wardrobe – Marine wc with safety valves.

Electrical system:

N. 2x80 A/h batteries – Power uses on electrical panel magnetothermal protected – battery swithc.

Fuel system and bilge pumps:

Lt. 326 stainless steel fuel tank with inspection cover – Fuel level guage on helm console – Copper fuel lines R.I.NA./CE certified flexible ends – Extra fuel filters – Fuel cut-off valves – Electrical extractor fan for engine and fuel tank compartment (petrol version) – N. 2 electrical bilge pumps 65 l/min qith manual control.

Water system:

Water tank in non-toxic polyethylene, capacity lt. 70 approx. – Water pump – Non electrical water heater lt.15 with safety valve.