

Tiara
Y A C H T S

3 0 0 0 O P E N



STANDARDS / OPTIONS

EFFECTIVE JULY 30, 2006
REVISED JANUARY 15, 2007

3000 OPEN

SPECIFICATIONS

L.O.A. without Standard Pulpit ...
30'6" - 9.29 meters

L.O.A. with Standard Pulpit ...
33'0" - 10.06 meters

L.O.A. with Standard Pulpit and Optional
30" Swim Platform ... 35'0" - 10.60 meters

Beam ... 12'6" - 3.81 meters

Draft (with Props) ... 2'8" - .8 meters

Approximate Dry Weight ...
w/ Crusader 8.1L 12,390 lbs. - 5,620 kg

Height from Waterline to Top of
Standard Hardtop ... 8'11" - 2.7 meters

Standard Fuel Capacity ...
210 U.S. gallons - 794.9 liters

Sleeping Accommodations ... 4

Water Capacity ...
32 U.S. gallons - 121.13 liters

Holding Tank Capacity ...
20 U.S. gallons - 75.71 liters

Cockpit Size ...
Upper: 55 sq. ft. - 5.1 sq. meters
Lower: 64 sq. ft. - 5.9 sq. meters

Deadrise at Transom ...14°

STANDARD EQUIPMENT

HULL, DECK AND UPPER COCKPIT

- Fresh white gelcoat hull and deck
- Tiara Yachts' transferable 5-year limited warranty on hull and deck
- Constructed with a gelcoat outer layer, and hand-laid fiberglass with a special blended, premium resin
- Wood and foam core stringers, encapsulated by hand-laid fiberglass, are integrated to hull
- Black gelcoat bootline with gold accent
- Bronze seacocks on all underwater thru-hull fittings
- Self-draining cockpit
- Molded-in hullside ventilation
- QL Marine® Interceptor boat trim system
- Four S.S. oval opening port lights with screens & privacy inserts

- Tiara custom diamond pattern non-skid deck and cockpit surfaces
- Molded-in fiberglass bow pulpit with S.S. roller system
- Flush forward anchor rope locker with overboard drain
- One (1) 8" S.S. foredeck cleat
- Automatic rope/chain anchor windlass system with operation from foredeck foot pedal and remote switch at helm
- One extruded aluminum and acrylic forward deck hatch with adjuster and built-in Ocean Air® screen and privacy cover
- One-piece welded 316L S.S. bow rail with pulpit, staff, and Tiara burgee
- Four (4) 10" 316L S.S. mooring cleats
- Two (2) 10" 316L S.S. spring cleats
- Two (2) corner oval hawse pipes
- Black rubrail with 316L S.S. cap
- Tiara custom composite windshield frame with tempered safety glass and 2 washer/wipers
- Tiara custom composite hardtop with solid front enclosure & insulating side enclosures. Includes safety handrails and port and starboard vent openings. Red & white lighting on the underside of the hardtop and two (2) aft facing spreader lights. Choice of cruising style arch/hardtop or aluminum fishing style arch/hardtop combination.
- Tiara hinged helm console with full flush mount electronics capability. One (1) drink holder.
- 12V outlet at helm
- Acrylic sliding companionway door with lock
- Fiberglass integrated shroud with navigation chart area and three (3) drink holders
- Drop-down engine room access hatch from the upper cockpit
- Helm back to back seat locker with forward seat and aft facing seat. Forward seat has manual actuator with 6 inches of fore and aft adjustment. Storage under forward seat cushion and additional storage access through aft-facing seat back. Two (2) drink holders & handrail between forward and aft facing seats.

- Companion seat - choice of:
1) Forward seat and aft workstation for entertaining and fishing. Workstation includes 20 gallon insulated storage, sprayer, cutting board and lid. Seven (7) cubic feet of storage under the workstation is accessible from a side door. Additional storage under forward facing seat cushion. Two drink holders and handrail between forward seat and work station.
or
2) Curved companion seat locker with storage below. Small work area aft with drink holders and safety handrail.
- 120V GFI outlet
- Helm console and seat covers

LOWER COCKPIT

- Fiberglass covering boards
- Cockpit coaming bolsters
- Cockpit courtesy lights
- Two (2) flush floor storage boxes, longitudinal, 1 port & 1 starboard
- Molded-in cockpit steps, port and starboard
- Dockside water inlet
- Fresh water washdown outlet with 25 ft. coiled blue hose
- Raw water washdown outlet with 25 ft. coiled yellow hose
- Transom door

INTERIOR GROUP

- Mold and mildew resistant vinyl hull and headliner
- Teak interior - *NOTE: Variations in Teak wood grain are natural, and cannot be controlled in the manufacturing process*
- Teak and holly veneer cabin sole
- 12V lighting
- 120V outlets throughout with cable TV/ phone outlet on port side of salon
- Clarion® AM/FM/CD stereo with remote, amp, 2 interior speakers and 4 cockpit speakers
- Plug-in port for MP3 player or IPOD



SALON

- Lounge and dinette seating with teak dinette table with high gloss finish to starboard. Converts to berth and includes a berth filler cushion.
- 6'4" headroom
- Companionway steps with hardwood treads, courtesy lights, and with S.S. companionway handrail
- Port locker with hanging rod and cedar back

GALLEY

- Formica® countertop with Corian® trim
- Stainless steel sink
- One-burner electric cooktop, surface mount

- Lower cabinet shelf storage with drawer above
- Microwave oven
- 2.3 cu ft./65 liter DC refrigerator with bins and bottle storage

FORWARD BERTH

- Double side berth with foam mattress, quilt, and 3 throw pillows
- Storage compartment under berth
- Two reading lights, independently switched

HEAD

- Full fiberglass head with shower curtain and shower sump pump
- Vanity with Corian® countertop, stainless steel sink and storage below
- Mirror
- Vacuflush® toilet with holding tank
- Exhaust blower & A/C vent

INSTRUMENTATION, EQUIPMENT AND SAFETY

- Tiara 12V and 120V distribution panels. The 120V panel is located under the companionway steps and the 12V panel is split between the companionway steps and the port hanging locker.
- One 120V 30 amp 65 ft. dockside power cord; inlet located port
- Cable TV/phone inlet and cabin outlet
- AM/FM antenna
- Charles® battery charger (1), 40 amp
- Two bank 12V battery system with batteries and battery switches (2 engine batteries and 2 house batteries)
- Reverse polarity indicators
- Amp meters, AC and DC
- Electrical bonding system
- Teleflex® hydraulic steering system with 16" S.S. destroyer wheel
- Teleflex® mechanical engine controls
- Bronze axe head rudders and struts
- Aquamer® S.S. prop shafts, 1 1/2" gas and 1 3/4" diesel
- Water cooled shaft logs with PSS® dripless shaft seal

- Two Nibral® propellers
- Zincs, transom and shafts
- Engine instrumentation: Crusader® engine option includes tachometers w/ hour meters, voltage gauges, fuel gauge, temperature gauges, and engine oil pressure gauges. Cummins® engine option includes voltage gauges, fuel gauge, and Smartcraft® engine monitoring display.
- Ritchie® Helmsman HF-743T compass
- Engine room acoustical insulation
- Engine hatch actuator
- Two Racor® fuel filters/water separators (diesel only)
- Two raw water intake strainers
- 12V engine room lights
- Twin Vernay® mufflers
- Two bilge blowers, 250 CFM each
- Three bilge pumps with monitors at helm - 1- 500 GPH automatic forward, 1- 2000 GPH automatic/manual mid, and 1- 2000 GPH automatic/manual aft
- Composite fuel tank with electric gauge, 210 gallons
- Fresh water tank, 32 gallons, with monitor located by companionway steps
- Water heater with exchanger, 6 gallons
- Holding tank, 20 gallons, with indicator light located in the head
- Air horn
- FE-241 agent fire extinguisher system in engine room (HFC-227 agent for CE)
- Three (3) handheld fire extinguishers
- Carbon monoxide detector (1)
- Smoke detector (1)
- Six 5/8" x 25' black dock lines
- Tiara life vests (4)
- Coast Guard Safety and Medical Kit
- U.S.C.G. and International lighting
- U.S.C.G. and B.I.A. ventilation
- NMMA Yacht Certification
- CE (European) Certification available for European Union countries

